


SEMICONDUCTOR RESISTANCE ELEMENT AND ITS MANUFACTURING METHOD

Patent number: JP8330514
Publication date: 1996-12-13
Inventor: OKUTO TAKASHI
Applicant: MATSUSHITA ELECTRIC WORKS LTD
Classification:
 - international: H01L27/04; H01L21/822
 - european:
Application number: JP19950129901 19950529
Priority number(s): JP19950129901 19950529

Report a data error here

Abstract of JP8330514

PURPOSE: To reduce the change in residue due to the ambient temperature change of a semiconductor resistance element over a wide temperature range by providing a polycrystalline silicon resistor with a negative temperature coefficient being connected to a single-crystalline diffusion resistor in series.
CONSTITUTION: The ratio of a length (a) of a polycrystalline silicon resistance region 4 to a length (b) of a P-type diffusion resistance region 2 is set to $a:b=tb:ta$ (ta : the temperature coefficient of a polycrystalline silicon resistor A which is constituted of the polycrystalline silicon resistance region 4, tb : the temperature coefficient of a P-type diffusion resistor B which is constituted of the P-type diffusion residue region 2). Then, the amount of change in the resistance of the P-type diffusion resistor B and that of the resistance of the polycrystalline silicon resistor A nearly cancel each other due to the change in ambient temperature, thus reducing the temperature coefficient of the semiconductor residue element and hence reducing the change in the resistance value.



Data supplied from the esp@cenet database - Worldwide